



Hi-Build Coatings Pvt. Ltd.

DURAKOTE INT PU HS CLEAR SEALER

It is a 2 pack PU Clear Sealer recommended for use on interior wooden furniture. High Solid PU Clear Sealer gives good transparency, elasticity and grain filling.

Typical Uses: It is developed for application on furniture, kitchen doors, frames, chairs etc. Always topcoat with PU clear finishes for best results

Type: 2 components Polyurethane Based Sealer

Application: Conventional Spraying/ Brushing

Viscosity B4 at 30° C: 115 - 125 sec

Application Viscosity: 18 - 20 Sec in B4 at 30°C

Specific Gravity at 30° C : 1.01 ± 0.03

Flash Point: Above 23°C

Solids content: 51% by weight

Mixing Ratio: 2:1 by volume, Base : 3342 Hardener, Thinner - Approx. 30 to 40% by volume

Pot Life - 2 to 3 Hrs at 30°C.

Amount to apply - 100 - 140 g /m²

Drying Time at 30°C: Surface Dry – 10 to 15 mts, Sanding Dry: 2 Hrs, Hard Dry – 5 to 6 hours

Characteristics of the applied product:

- Filling Power : Very Good
- Flow Leveling :Excellent
- Elasticity: Good
- Sandability: Excellent

Safety directions/Precautions: It is the precise responsibility of the user to ensure that the application takes place in an adequately ventilated environment and in the observance of the hygienic and safety regulations.

Packing - 30 Ltr (20 ltr Base + 10 ltr Hardner)

Shelf Life: 12 months from the production date, in the original packing and at the conditions mentioned in storage indications

Storage Indications: Store in a cool, dry & well ventilated place away from moisture, heat & direct sunlight.

Health & Safety information: Fire hazard class: Highly Inflammable

Health hazard class: NONE, but the product contains volatile, organic solvents