



DURAKOTE INT PU TOPCOAT CLEAR GLOSSY

It is a 2 pack PU Topcoat recommended for use on interior wooden furniture. High Solid PU Clear Topcoat is very transparent & is characterized by a high mar resistance and has very good light fastness properties.

Typical Uses: It is specially developed for cabinet doors & furniture

Available Finishes: Glossy

Type: Two component Polyurethane Based Top Coat

Application: Conventional Spraying/ Brushing

Viscosity B4 at 30° C: 80 - 90 sec

Application Viscosity: 18 - 20 Sec in B4 at 30°C

Specific Gravity at 30° C: 1.00 ± 0.02

Flash Point: Above 23°C

Solids content: 49-50% by weight

Mixing Ratio: 2:1 by volume Base : 3399 Hardener, Thinner - Approx. 40 to 50% by volume

Pot Life - 2 to 3 Hrs at 30°C.

Amount to apply - 110 - 140 g /m²

Drying Time at 30°C: Surface Dry – 10 to 15 mts, Sanding Dry: 4 to 5 Hrs, Hard Dry – Overnight

Characteristics of the applied product:	Gloss Hold out – Very Good
	Filling Power: Very Good
	Flow Leveling: Excellent
	Elasticity: Good
	Mar Resistance: Very Good

Safety directions/Precautions: It is the precise responsibility of the user to ensure that the application takes place in an adequately ventilated environment and in the observance of the hygienic and safety regulations.

Packing - 30 Ltr (20 ltr Base + 10 ltr Hardner)

Shelf Life: 12 months from the production date, in the original packing and at the conditions mentioned in storage indications

Storage Indications: Store in a cool, dry & well ventilated place away from moisture, heat & direct sunlight.

Health & Safety information: Fire hazard class: Highly Inflammable

Health hazard class: NONE, but the product contains volatile, organic solvents