



SLEEK NEO WB SEALER CLEAR

Typical Uses: It is used as a water based sealer coat on all types of wood for furniture & joinery for interior & exterior use

Type: Water Based

Specific Gravity at 30° C: 1.03 ± 0.02

Solids content: 33% by weight

Viscosity: 130 ± 10 sec in B4 Cup at 30° C

Application Viscosity: 20 - 25 Sec in B4 at 30°C

Application: Conventional Spraying, Brushing, Roller & Dipping

Flash Point: Above 75° C

Dilution: Can dilute with 10 to 15% potable water

Substrate: Can be applied on different kinds of Timbers & Veneers sanded with 180 to 220 grit abrasive & cleaned from dust.

For Tannin rich timber like Teak & Rosewood it is ideal to put one coat of WB Insulating Sealer as Barrier Coat, before the sealer, to prevent bleeding of oil, discoloration & coating failure. WB Insulating Sealer is a one pack system, applied by Brush or Spray.

Amount to apply: 80 - 100 g /m²

Suggested No. of Coats: 2

Time between Coats: 2 hours

Intermediate sanding with: 220 / 320 grit

Drying Time at 30° C: Surface Dry – 20 to 30 mts, Sanding Dry: 1 - 2 Hrs, Hard Dry – 5 to 6 hours

Force Drying Schedule: Flash Off – 10 mts, Oven Dry 40 to 50° C- 20 to 30 mts, Room Temperature – 10 mts

The above drying times are valid provided the relative humidity & circulation of air are suitable for release of water from the applied layer

Relative humidity: 40 to 75 %

Characteristics of the applied product: Sandability: Excellent

Flow Leveling : Excellent

Elasticity: Good

Packing - 20 Lt & 1 ltr

Shelf Life: 12 months from the production date, in the original packing and at the conditions mentioned in storage indications

Storage Indications: Store in a cool, dry & well ventilated place away from moisture, heat & direct sunlight.